



Syntax and Messages

Stéphane Ducasse
Stephane.Ducasse@univ-savoie.fr
<http://www.iam.unibe.ch/~ducasse/>

Outline

- **Literals: numbers, strings, arrays....**
- Variable, assignments, returns
- Pseudo-variables
- Message Expressions
- Block expressions
- Conditional and Loops



Originally Made for Kids

Read it as a non-computer-literate person:

```

| bunny |
bunny := Actor fromFile:'bunny.vrml'.
bunny head doEachFrame:
[ bunny head
  pointAt: (camera
    transformScreenPointToScenePoint:
      (Sensor mousePoint)
    using: bunny)
  duration: camera rightNow ]

```



Numbers

- SmallInteger, Integer,
 - 4, 2r100 (4 in base 2), 3r11 (4 in base 3), 1232
- Automatic coercion
 - 1 + 2.3 -> 3.3
 - 1 class -> SmallInteger
 - 1 class maxVal class -> SmallInteger
 - (1 class maxVal + 1) class -> LargeInteger
- Fraction, Float, Double
 - 3/4, 2.4e7, 0.75d
 - (1/3) + (2/3) -> 1
 - 1000 factorial / 999 factorial -> 1000
 - 2/3 + 1 -> (5/3)



Characters

- Characters:
 - \$F, \$Q \$U \$E \$N \$T \$i \$N
- Unprintable characters:
 - Character space, Character tab, Character cr



Strings



- Strings:
 - #mac asString -> 'mac'
 - 12 printString -> '12'
 - 'This packet travelled around to the printer' 'I"idiot'
 - String with: \$A
 - Collection of characters
 - 'lulu' at: 1 -> \$!
- To introduce a single quote inside a string, just double it.



Symbols

- Symbols:
 - #class #mac #at:put: #+ #accept:
- Kinds of String
- Unique in the system (see after)



Symbols vs. Strings

- Symbols are used as method selectors, unique keys for dictionaries
- A symbol is a read-only object, strings are mutable objects
- A symbol is unique, strings are not


```

#calvin == #calvin -> true
'calvin' == 'calvin' -> false
#calvin, #zeBest -> 'calvinzeBest'

```
- Symbols are good candidates for identity based dictionaries (IdentityDictionary)
- Hint: Comparing strings is slower than comparing symbols by a factor of 5 to 10. However, converting a string to a symbol is more than 100 times more expensive.



Comments and Tips

- "This is a comment"
- A comment can span several lines. Moreover, avoid putting a space between the " and the first character. When there is no space, the system helps you to select a commented expression. You just go after the " character and double click on it: the entire commented expression is selected. After that you can printlt or dolt, etc.



Arrays

- `#(1 2 3) #'(lulu' (1 2 3)) -> #'(lulu' #(1 2 3))`
- `#(mac node1 pc node2 node3 lpr)` an array of symbols.
- When one prints it it shows `#(#mac #node1 #pc #node2 #node3 #lpr)`
- Byte Array `#[1 2 255]`

S.Ducasse



Arrays

- Heterogenous
 - `#'(lulu' (1 2 3)) -> #'(lulu' #(1 2 3))`
 - `#'(lulu' 1.22 1) -> #'(lulu' 1.22 1)`
- An array of symbols:
 - `#(calvin hobbes suzie) -> #(#calvin #hobbes #suzie)`
- An array of strings:
 - `#'(calvin' 'hobbes' 'suzie) -> #'(calvin' 'hobbes' 'suzie)`

S.Ducasse



Syntax Summary

```
comment: "a comment"
character: $c $h $a $r $s $t $e $r $s $# $@
string: 'a nice string' 'lulu' '!"'idiot'
symbol: #mac #+
array: #(1 2 3 (1 3) $a 4)
byte array: #[1 2 3]
integer: 1, 2r101
real: 1.5, 6.03e-34.4, 2.4e7
float: 1/33
boolean: true, false
point: 10@120
```

Note that @ is not an element of the syntax, but just a message sent to a number. This is the same for /, biShift, ifTrue:, do: ...

S.Ducasse

12

Roadmap

- Literals: numbers, strings, arrays...
- **Variable, assignments, returns**
- Pseudo-variables
- Message Expressions
- Block expressions
- Conditional and Loops




S.Ducasse

13



Variables

- Maintains a reference to an object
- Dynamically typed and can reference different types of objects
- Shared (starting with uppercase) or local (starting with lowercase)



S.Ducasse



Temporary Variables

- To hold temporary values during evaluation (method execution or sequence of instructions)
- Can be accessed by the expressions composing the method body.
 - `| mac1 pc node1 printer mac2 packet |`

S.Ducasse



Temporary Variable Good Style

- Avoid using the same name for a temporary variable and a method argument, an instance variable or another temporary variable or block temporary. Your code will be more portable. Do not write:

```
aClass>>printOn: aStream
|aStream|
...
```

- Instead, write:

```
aClass>>printOn: aStream
|anotherStream|
...
```

- Hint: Avoid using the same temporary variable for referencing two different objects

S.Ducasse



Assignments

- An Assignment is not done by message passing. It is one of the few syntactic elements of Smalltalk.

```
variable := aValue
three := 3 raisedTo: 1
variable1 := variable2 := aValue
```

- Avoid using `var := var2 := var3`
- To not try to know in which order the expressions is evaluated. You will write good code

S.Ducasse



Pointing to the Same Object

- In Smalltalk, objects are manipulated via implicit pointers: everything is a pointer.
- Take care when different variables point to the same object:

```
p1 := p2 := 0@100
p1 x: 100
p1 -> 100@100
p2 -> 100@100
```

S.Ducasse



Method Arguments

- Can be accessed by the expressions composing the method.
- Exist during the execution of the defining method.
- Method Name Example:
accept: aPacket
- In C++ or Java:
void Printer::accept(aPacket Packet)

S.Ducasse



Arguments are read-only

- Method arguments cannot change their value within the method body.
- Invalid Example, assuming contents is an instance variable:

```
MyClass>>contents: aString  
aString := aString, 'From Lpr'.
```

- Valid Example

```
MyClass>>contents: aString  
| addressee |  
addressee := aString, 'From Lpr'
```

S.Ducasse



Method Return



Use ^ expression to return the value of expression from a method

```
Rectangle>>area
```

```
^ width * height
```

By default self is returned

S.Ducasse

21



Instance Variables



- Private to a particular instance (not to all the instances of a class like in C++).
- Can be accessed by all the methods of the defining class and its subclasses.
- Has the same lifetime as the object.
- Declaration

```
Object subclass: #Node  
instanceVariableNames: 'name nextNode '  
...
```

S.Ducasse



Instance Variables

- Scope: all the methods of the class

```
Node>>setName: aSymbol nextNode: aNode  
name := aSymbol.  
nextNode := aNode
```

- But preferably accessed using accessor methods

```
Node>>name  
^name
```

S.Ducasse



Global Variables

- Always Capitalized (convention)
 - MyGlobalPi := 3.1415
- If it is unknown, Smalltalk will ask you if you want to create a new global
 - Smalltalk at: #MyGlobalPi put: 3.14
 - MyGlobalPi
-> 3.14
 - Smalltalk at: #MyGlobalPi
-> 3.14
- Stored in the default environment: Smalltalk in Squeak, VW has namespaces
- Design Hints: Accessible from everywhere, but it is not a good idea to use them

S.Ducasse



Roadmap

- Literals: numbers, strings, arrays...
- Variable, assignments, returns
- **Pseudo-variables**
- Message Expressions
- Block expressions
- Conditional and Loops



S.Ducasse

25



Six Pseudo-Variables

- Smalltalk expressions can contain true, false, nil, self, super thisContext, but cannot change their values. They are hardwired into the compiler.
- nil nothing, the value for the uninitialized variables. Unique instance of the class UndefinedObject

S.Ducasse



Six Pseudo-Variables



- **true**
 - unique instance of the class True
- **false**
 - unique instance of the class False
- Hint: Don't use False instead of false. false is the boolean value, False the class representing it. So, the first produces an error; the second not:
 - False ifFalse: [Transcript show: 'False'] -> error
 - false ifFalse: [Transcript show: 'False']

S.Ducasse



self, super, and thisContext

- Only make sense in a method body
- **self** refers to the receiver of a message.
- **super**
 - refers also to the receiver of the message but its semantics affects the lookup of the method. It starts the lookup in the superclass of the class of the method containing the super.
- **thisContext**
 - refers to the instance of MethodContext that represents the context of a method (receiver, sender, method, pc, stack). Specific to VisualWorks and to Squeak

S.Ducasse



self and super examples

```
PrinterServer>>accept: thePacket
"If the packet is addressed to me, print it.
Otherwise behave normally."
```


```
(thePacket isAddressedTo: self)
ifTrue: [self print: thePacket]
ifFalse: [super accept: thePacket]
```

S.Ducasse



Roadmap

- Literals: numbers, strings, arrays...
- Variable names
- Pseudo-variables
- Assignments, returns
- **Message Expressions**
- Block expressions
- Conditional and Loops



S.Ducasse

30



Objects and Messages

- Objects communicate by sending message
- Objects react to messages by executing methods

```
Bot new go: 30 + 50
```

- A message is composed of:
 - a receiver, always evaluated (Bot new)
 - a selector, never evaluated #go:
 - and a list possibly empty of arguments that are all evaluated (30 + 50)
- The receiver is linked with self in a method body.

S.Ducasse



Three Kinds of Messages



- Unary Messages
 - 2.4 inspect
 - macNode name
- Binary Messages
 - 1 + 2 -> 3
 - (1 + 2) * (2 + 3) -> 15
 - 3 * 5 -> 15
- Keyword Messages
 - 6 gcd: 24 -> 6
 - pcNode nextNode: node2
 - Turtle new go: 30 color: Color blue

S.Ducasse



Unary Messages

aReceiver aSelector

```
node3 nextNode -> printerNode
node3 name -> #node3
1 class -> SmallInteger
false not -> true
Date today -> Date today September 19, 1997
Time now -> 1:22:20 pm
Double pi -> 3.1415926535898d
```

S.Ducasse



Binary Messages

aReceiver aSelector anArgument

- Used for arithmetic, comparison and logical operations
- One or two characters taken from:
 - + - / * ~ < > = @ % | & ! ? ,
 - 1 + 2
 - 2 >= 3
 - 100@100
 - 'the', 'best'
- Restriction:
 - second character is never \$-

S.Ducasse



Simplicity has a Price

- no mathematical precedence so take care

```
3 + 2 * 10 -> 50
3 + (2 * 10) -> 23
(1/3) + (2/3) and not
1/3 + 2/3
```

S.Ducasse



Keyword Messages

receiver

keyword1: argument1
keyword2: argument2

```
1 between: 0 and: 5
dict at: #blop put: 8+3
```

- In C-like languages it would be:
receiver.keyword1 keyword2... (argument1 type1, argument2, type2) : return-type

S.Ducasse



Keyword Messages

Workstation **withName:** #Mac2
mac **nextNode:** node1
Packet
send: 'This packet travelled around to'
to: #w100
|@1 **setX:** 3
#(1 2 3) **at:** 2 **put:** 25
1 **to:** 10 -> (1 to: 10) anInterval
Browser **newOnClass:** Point
Interval **from:** 1 **to:** 20 -> (1 to: 20)
12 **between:** 10 **and:** 20 -> true
x > 0 **ifTrue:**['positive'] **ifFalse:**['negative']

S.Ducasse



Composition Rules



- **Unary-Msg > Binary-Msg > Keywords-Msg**
 - at same level, from the left to the right
- 2 + 3 squared -> 11
2 raisedTo: 3 + 2 -> 32
#(1 2 3) at: 1+1 put: 10 + 2 * 3 -> #(1 36 3)
- 2 raisedTo: 3 + 2 <=> (2 raisedTo: (3+2)) -> 32

S.Ducasse



Composition Rules

- **(Msg) > Unary-Msg > Binary-Msg > Keywords-Msg**
- 69 class inspect
(0@0 extent: 100@100) bottomRight

S.Ducasse



Hints ...

- Use () when two keyword-based messages
- occur within a single expression, otherwise the precedence order is fine.
 - x isNil ifTrue: [...]
- **isNil** is an unary message, so it is evaluated prior to **ifTrue:**
 - x includes: 3 ifTrue: [...]
- is read as the message includes:ifTrue:
 - (x includes: 3) ifTrue: [...]
- We use () to disambiguate them

S.Ducasse



Sequence

```
message1 .  
message2 .  
message3  
.  
is a separator, not a terminator
```

```
| macNode pcNode node1 printerNode |  
macNode := Workstation withName: #mac.  
Transcript cr.  
Transcript show: 1 printString.  
Transcript cr.  
Transcript show: 2 printString
```

S.Ducasse



For the Lazy: the Cascade

```
receiver  
selector1;  
selector2; ...
```

- To send multiple messages to the same object

```
Transcript show: 1 printString.  
Transcript show: cr
```

- is equivalent to:

```
Transcript show: 1 printString ; cr
```

S.Ducasse



Syntax Summary

assignment: var := aValue
unary message: receiver selector
binary message: receiver selector argument
keyword based: receiver keyword1: arg1 keyword2:
arg2...
cascade: message ; selector ...
separator: message . message
result: ^
parenthesis: (...)

S.Ducasse

43

Roadmap

- Literals: numbers, strings, arrays...
- Variable, assignments, returns
- Pseudo-variables
- Message Expressions
- **Block expressions**
- Conditional and Loops



S.Ducasse

44



Blocks



- **anonymous methods**
- **deferred block of code**

```
fct(x) = x ^ 2 + x  
fct (2) = 6  
fct (20) = 420
```

```
[fct]  
fct:= [:x | x * x + x].  
fct value: 2 -> 6  
fct value: 20 -> 420  
fct -> aBlockClosure
```

S.Ducasse



Blocks Continued

```
[ :variable | :variable2 |  
  | blockTemporary | blockTemporary2 |  
  expression1.  
  ...variable | ... ]
```

- Two blocks without arguments and temporary variables

```
PrinterServer>>accept: thePacket  
  (thePacket isAddressedTo: self)  
  ifTrue: [self print: thePacket]  
  ifFalse: [super accept: thePacket]
```

S.Ducasse



Block Evaluation

```
[...] value  
  or value: (for one arg)  
  or value:value: (for two args)  
  or value:value:value: ...  
  or valueWithArguments: anArray
```

```
[2 + 3 + 4 + 5] value  
[x | x + 3 + 4 + 5] value: 2  
[x :y | x + y + 4 + 5] value: 2 value: 3  
[x :y :z | x + y + z + 5] value: 2 value: 3 value: 4  
[x :y :z :w | x + y + z + w] value: 2 value: 3 value: 4 value: 5
```

S.Ducasse



Block

- The value of a block is the value of its last statement, except if there is an explicit return ^
- Blocks are first class objects.
- They are created, passed as argument, stored into variables...

S.Ducasse



Blocks - Continued

```
|index bloc |  
index := 0.  
bloc := [index := index + 1].  
index := 3.  
bloc value -> 4
```

```
Integer>>factorial  
"Answer the factorial of the receiver. Fail if the receiver is  
less than 0."  
| tmp |  
....  
tmp := 1.  
2 to: self do: [i | tmp := tmp * i].  
^tmp
```

S.Ducasse



- Literals: numbers, strings, arrays...
- Variable, assignments, returns
- Pseudo-variables
- Message Expressions
- Block expressions
- **Conditional and Loops**



S.Ducasse

50



Yes ifTrue: is sent to a boolean

```
Weather isRaining  
ifTrue: [self takeMyUmbrella]  
ifFalse: [self takeMySunglasses]
```

ifTrue:ifFalse is sent to an object: a boolean!

S.Ducasse

51



Conditional: messages to booleans

- aBoolean **ifTrue:** aTrueBlock **ifFalse:** aFalseBlock
- aBoolean **ifFalse:** aFalseBlock **ifTrue:** aTrueBlock
- aBoolean **ifTrue:** aTrueBlock
- aBoolean **ifFalse:** aFalseBlock

```
(thePacket isAddressedTo: self)  
ifTrue: [self print: thePacket]  
ifFalse: [super accept: thePacket]
```

- Hint: Take care — true is the boolean value and True is the class of true, its unique instance!

S.Ducasse



Boolean Messages

- Logical Comparisons: &, |, xor:, not
aBooleanExpr comparison **aBooleanExpr**
 - (1 isZero) & false
 - Date today isRaining not
- Uniform, but optimized and inlined (macro expansion at compile time)
- aBooleanExpression **or:** orBlock
orBlock will **only** be evaluated if aBooleanExpression is false
false and: [1 error: 'crazy']
-> false and not an error

S.Ducasse

53



Yes a collection is iterating on itself

```
 #(1 2 -4 -86)  
  do: [:each | Transcript show: each abs  
  printString ;cr ]
```

```
> 1  
> 2  
> 4  
> 86
```

Yes we ask the collection object to perform the loop on itself

S.Ducasse

54



Some Basic Loops

- aBlockTest whileTrue
- aBlockTest whileFalse
- aBlockTest whileTrue: aBlockBody
- aBlockTest whileFalse: aBlockBody
- anInteger timesRepeat: aBlockBody

- [x<y] whileTrue: [x := x + 3]

- 10 timesRepeat: [Transcript show: 'hello'; cr]

S.Ducasse

55



For the Curious...

```
BlockClosure>>whileTrue: aBlock
  ^ self value
  ifTrue:[ aBlock value.
          self whileTrue: aBlock ]
```

```
BlockClosure>>whileTrue
  ^ [ self value ] whileTrue:[]
```

S.Ducasse

56



For the Curious...

```
Integer>>timesRepeat: aBlock
  "Evaluate the argument, aBlock, the number of
  times represented by the receiver."
```

```
| count |
count := 1.
[count <= self] whileTrue:
  [aBlock value.
   count := count + 1]
```

S.Ducasse

57



Choose your Camp!

To get all the absolute values of numbers you could write:

```
|result|
aCol := ( 2 -3 4 -35 4 -11).
result := aCol species new: aCol size.
1 to: aCollection size do:
  [ :each | result
    at: each put: (aCol at: each) abs].
result
```

S.Ducasse

58



Choose your Camp (II)

- You could also write:

```
( 2 -3 4 -35 4 -11) collect: [ :each | each abs ]
```

- Really important: Contrary to the first solution, the second solution works well for indexable collections and also for sets.

S.Ducasse

59



Iteration Abstraction: do:/collect:

```
aCollection do: aOneParameterBlock
aCollection collect: aOneParameterBlock
aCollection with: anotherCollection do:
aBinaryBlock
```



```
(15 10 19 68) do:
  [i | Transcript show: i printString ; cr ]
```

```
(15 10 19 68) collect: [i | i odd ]
-> (true false true false)
```

```
(1 2 3) with: (10 20 30)
do: [x :y] Transcript show: (y ** x) printString ; cr ]
```

S.Ducasse

60



Opening the Box

Iterators are messages sent to collection objects
Collection is responsible of its traversal

```
SequenceableCollection>>do: aBlock
  "Evaluate aBlock with each of the receiver's elements
  as the argument."
```

```
1 to: self size do: [i | aBlock value: (self at: i)]
```

S.Ducasse

61



select:/reject:/detect:

```
aCollection select: aPredicateBlock
aCollection reject: aPredicateBlock
aCollection detect:
aOneParameterPredicateBlock
aCollection
  detect: aOneParameterPredicateBlock
  ifNone: aNoneBlock
```

```
(15 10 19 68) select: [:i|i odd] -> (15 19)
(15 10 19 68) reject: [:i|i odd] -> (10 68)
(12 10 19 68 21) detect: [:i|i odd] -> 19
(12 10 12 68) detect: [:i|i odd] ifNone:[1] -> 1
```

S.Ducasse

62



inject:into:

```
aCollection inject: aStartValue into: aBinaryBlock
```

```
| acc |
acc := 0.
(1 2 3 4 5) do: [:element | acc := acc + element].
acc
-> 15
```

```
Is equivalent to
(1 2 3 4 5)
  inject: 0
  into: [:acc :element| acc + element]
-> 15
```

Do not use it if the resulting code is not crystal clear!

S.Ducasse

63



Other Collection Methods

aCollection includes: anElement

aCollection size

aCollection isEmpty

aCollection contains: aBooleanBlock

(1 2 3 4 5) includes: 4 -> true

(1 2 3 4 5) size -> 5

(1 2 3 4 5) isEmpty -> false

(1 2 3 4 5) contains: [:each | each isOdd] -> true



What we saw

- Numbers (integer, real, float...), Character \$a, String 'abc', Symbols (unique Strings) #jkk,
- Arrays (potentially not homogenous) #(a #(1 2 3), Array with: 2+3
- Variables:
 - Lowercase => private
 - Instance variables (visible in by all methods), method arguments (read-only), local variable [a]
 - Uppercase => global
- Pseudo Var: true, false, nil, self, super
 - self = ****always**** represents the msg receiver
 - nil = undefined value

What we saw

- Three kinds of messages
 - Unary: Node new
 - Binary: 1 + 2, 3@4
 - Keywords: aTomagoshi eat: #cooky furiously: true
- (Msg) > unary > binary > keywords
- Same Level from left to right
- Block
 - Functions
 - fct(x)= x*x+3, fct(2).
 - fct :=[:x| x * x + 3]. fct value: 2
 - Anonymous method
 - Passed as method argument:

```
factorial
tmp:= 1.
2 to: self do: [:i| tmp := tmp * i]
```