



Naming Smalltalk Patterns



Stéphane Ducasse

Stephane.Ducasse@univ-savoie.fr

<http://www.iam.unibe.ch/~ducasse/>

Coding Standards

- Mainly from Smalltalk Best Practice Patterns by K. Beck
- Excellent
- Must read!



Coding Standards

- Standards
 - improve communication
 - let code be the design
 - make code more habitable
 - change



Coding Standards for Smalltalk

- Variables have no types
- Names can be any length
- Operations named with keywords
- Pretty printer



Names

- Names should mean something.
- Standard protocols
 - Object (printOn:, =)
 - Collection (do:, add:, at:put:, size)
- Standard naming conventions



Intention Revealing Selector

- Readability of message send is more important than readability of method
- Name should specify what method does, not how.



- aDoor open
- and not
- aDoor putPressureOnHandleThenPullWithRotation

Examples

ParagraphEditor>>**highlight**: aRectangle
self reverse: aRectangle

If you would replace **highlight**: by **reverse**:. , the system will run in the same way but you would reveal the implementation of the method.



Examples

If we choose to name after HOW it accomplished its task

Array>>linearSearchFor;

Set>>hashedSearchFor;

BTree>>treeSearchFor:

These names are not good because you have to know the type of the objects.

Collection>>searchFor:

even better

Collection>>includes:



Name your Method Well

Instead of:

```
setTypeList: aList
```

```
"add the aList elt to the Set of type taken by the variable"
```

```
typeList add: aList.
```

Write:

```
addTypeList: aList
```

```
"add the aList elt to the Set of type taken by the variable"
```

```
typeList add: aList.
```



Name Well your Methods

setType: aVal

"compute and store the variable type"

self addTypeList: (ArrayType with: aVal).

currentType := (currentType computeTypes: (ArrayType with: aVal))

Not precise, not good

computeAndStoreType: aVal

"compute and store the variable type"

self addTypeList: (ArrayType with: aVal).

currentType := (currentType computeTypes: (ArrayType with: aVal))

Precise, give to the reader a good idea of the
functionality and not about the implementation



Method Names



Method Names

- If there is already a **standard** name, use it otherwise follow these rules.
- Three kinds of methods
 - change state of receiver
 - change state of argument
 - return value from receiver



Change State of Receiver

- method name is verb phrase
 - translateBy:
 - add:



Change State of Argument

- Verb phrase ending with preposition like **on** or **to**.
 - displayOn:
 - addTo:
 - printOn:



Return Value from Receiver

- Method name is noun phrase or adjective, a description rather than a command
 - translatedBy:
 - size
 - topLeft



Method Names

- Specialized names for specialized purposes.
 - Double-dispatching methods
 - Accessing methods
 - Query methods
 - Boolean property setting
 - Converter methods



Accessing Methods

- Many instance variables have accessing methods, methods for reading and writing them.
- Same name than the instance variables
- Accessing methods come in pairs.
 - name, name:
 - width, width:
 - x, x:



When to use Accessing Methods

- Two opinions:
 - Always, including an object's own instance variable
 - lazy initialization, subclassing is easier
 - Only when you need to use it.
 - better information hiding
 - With the refactoring browser it is easy to transform the class using or not accessing



Query Method

- Methods that return a value often describe the type of the value because they are noun phrases.
- Query methods are not noun phrases, but are predicates.
- How can we make the return type clear?
- Provide a method that returns a Boolean in the “testing” protocol. Name it by prefacing the property name with a form of “be” or “has” - is, was, will, has



Testing Methods

- Prefix every testing method with "is".
 - isNil
 - isControlWanted
 - isEmpty
 - hasBorder



Converting Method

- Often you want to return the receiver in a new format.
- Prepend "as" to the name of the class of object returned.
 - asSet (in Collection)
 - asFloat (in Number)
 - asComposedText (in Text)



Classes



Simple Superclass Name

- What should we call the root of a hierarchy?
 - Complex name conveys full meaning.
 - Simple name is easy to say, type, extend.
 - But need to show that subclasses are related.



Simple Superclass Name

- Give superclasses simple names: two or (preferably) one word
 - Number
 - Collection
 - VisualComponent



Qualified Subclass Name

- What should you call a subclass that plays a role similar to its superclass?
 - Unique name conveys most information
 - Derived name communicates relationship to superclass



Qualified Subclass Name

- Use names with obvious meaning. Otherwise, prepend an adjective to most important superclass.
 - OrderedCollection
 - UndefinedObject
 - CloneFigureCommand, CompositeCommand, ConnectionCommand





Variables: Roles vs. Types

- Types are specified by classes
 - aRectangle
 - aCollection
 - aView
- Roles - how an object is used
 - location
 - employees
 - topView



Role Suggesting Instance Variable

- What should you name an instance variable?
 - Type is important for understanding implementation. But class comment can describe type.
 - Role communicates intent, and this harder to understand than type.



Role Suggesting Instance Variable

- Name instance variables for the role they play. Make the name plural if the variable is a collection.
 - Point: x, y
 - Interval: start, stop, step
 - Polyline: vertices



Type Suggesting Parameter Name

- Name of variable can either communicate type or role.
- Keywords communicate their parameter's role, so name of variable should give new information.



Type Suggesting Parameter Name

- Name parameters according to their most general expected class, preceded by "a" or "an". If there is more than one parameter with the same expected class, precede the class with a descriptive word.



Temporaries

- Name temporaries after role they play.
- Use temporaries to:
 - collect intermediate results
 - reuse result of an expression
 - name result of an expression
- Methods are simpler when they don't use temporaries!



Conclusion

Names are important
Programming is about
communication
intention

...

Read the book:

Smalltalk Best Practice Patterns

Even if you will program in Java or C#!

When the program compiles this is the start not the
end...