#### **Advanced Object-Oriented Design**

# Did You Really Understand Super?

S. Ducasse and L. Fabresse





# What you will learn

#### Revisit

- super
- Message lookup
- Class methods



#### A little puzzle

```
Die class >> new
```

```
| inst |
inst := super new.
inst initialize.
^ inst
```

We execute the following expression: Die new

#### **Questions**

```
Die class >> new
```

```
| inst |
inst := super new.
inst initialize.
^ inst
```

- What is inst?
- What is super?
- What is super new?

#### **Hint: super is Not...**

```
Die class >> new
```

```
| inst |
inst := super new.
inst initialize.
^ inst
```

- No super is not the superclass
- No inst is not an instance of the superclass


## Hint 2: super is the message receiver

```
Die class >> new
```


```
| inst |
inst := super new.
inst initialize.
```

- ^ inst
- The message is Die new
- So the receiver is the class Die

# Sending a message: Lookup + execute on receiver



## **Remember: Method lookup**




#### **Solution**

```
Die class >> new
```

```
| inst |
inst := super new.
inst initialize.
^ inst
```

- super is the receiver: the class Die
- Look for new in the superclass of the class Die class (Pay attention not Die)
- Once found we apply to the receiver: Die
- We get an instance of the class Die and send it initialize and return it

#### **Solution**



## **Summary**

- Sending a message is looking up for the method and applying it on the receiver
- Now you should really understand super :)
- super is the receiver of the message and the method lookup starts in the superclass of the class containing the expression

### **Challenge yourself**

Imagine we have:

A >> foo

^ super class == self class

What is the result of A new foo and why?

#### A course by

#### S. Ducasse, G. Polito, and Pablo Tesone



