


Shared variables

A Pharo code idiom

S.Ducasse, L. Fabresse, G. Polito, and P. Tesone



<http://www.pharo.org>



Goals

- Revisit *shared* variables (e.g., ClassVariables in Smalltalk jargon)
- Think about scope of sharing



Instance variables are local to one object

Nothing new!

- An instance variable value is **only accessible and local** to the object it belongs to
- If you modify an instance variable, you only modify that variable



Shared variables are shared by all the instances of a hierarchy

- All the instances of a class and its subclasses **share the SAME** shared variable
- If you modify a shared variable, it impacts all the instances
- A shared variable is usually initialized at class load time (class initialize method)
- Shared variables
 - called ClassVariables in Smalltalk
 - called SharedVariables in Pharo



Color example

All the instances of Color and its subclasses share ComponentMask

```
Object << #Color
slots: { #rgb . #cachedDepth . #cachedBitPattern . #alpha };
sharedVariables: { #RedShift . #CachedColormaps . #IndexedColors .
#ComponentMax . #ComponentMask . #ColorRegistry . #GreenShift . #BlueShift };
package: 'Colors'
```



Color's ComponentMask is a shared variable

privateBlue

"Private! Return the internal representation
of my blue component."

^ **rgb** bitAnd: **ComponentMask**

Color
rgb
alpha
ColorRegistry
ComponentMask
privateBlue
...

instanceOf

Color class
initialize

initialize

```
ComponentMask := 1023.  
HalfComponentMask := 512.  
ComponentMax := 1023.0.  
RedShift := 20.  
GreenShift := 10.  
BlueShift := 0.  
RandomStream := Random new.  
self initializeIndexedColors.  
self initializeColorRegistry.  
self initializeGrayToIndexMap.
```

Shared variables: accessible from instance methods

Color >> setRed: r green: g blue: b

"Initialize this color's r, g, and b components to the given values in the range [0.0..1.0].

Encoded in a single variable as 3 integers in [0..1023]."

rgb == nil ifFalse: [self attemptToMutateError].

rgb := (((r * ComponentMax) rounded bitAnd: ComponentMask) bitShift: RedShift)
+ (((g * ComponentMax) rounded bitAnd: ComponentMask) bitShift: GreenShift)
+ ((b * ComponentMax) rounded bitAnd: ComponentMask).

cachedDepth := nil.

cachedBitPattern := nil



Shared variables: accessible from class methods

Color class >> initialize

ComponentMask := 1023.

HalfComponentMask := 512. "used to round up in integer calculations"

ComponentMax := 1023.0. "a Float used to normalize components"

RedShift := 20.

GreenShift := 10.

BlueShift := 0.


self initializeIndexedColors.

self initializeColorRegistry.

self initializeGrayToIndexMap.



Shared variable example: String



Shared Variables of String

```
ArrayedCollection << #String  
    sharedVariables: { #CaseSensitiveOrder . #CSSeparators .  
        #CSNonSeparators . #UppercasingTable .  
        #CSLineEnders . #LowercasingTable . #CaseInsensitiveOrder .  
        #TypeTable . #Tokenish . #AsciiOrder };  
    package: 'Collections-Strings'
```



Shared variable CaseSensitiveOrder accessed in subclass method

ByteSymbol >> beginsWith: prefix

"Answer whether the receiver begins with the given prefix string.
The comparison is case-sensitive."

prefix class isBytes ifFalse: [^super beginsWith: prefix].

self size < prefix size ifTrue: [^ false].

^ (self findSubstring: prefix in: self startingAt: 1
matchTable: CaseSensitiveOrder) = 1



Shared variable accessed in subclass class method

Symbol class >> selectorsContaining: aString

"Answer a list of selectors that contain aString within them. Case-insensitive.
Does return symbols that begin with a capital letter."

...

```
self allSymbolTablesDo: [:each |  
    each size >= size ifTrue:  
        [(each findSubstring: aString in: each startingAt: 1  
            matchTable: CaseInsensitiveOrder) > 0  
            ifTrue: [selectorList add: each]]].
```

...



Implications

- There is a difference between Shared variables and instance variable of the metaclass
- There is a difference between:

```
Object << #BorderStyle  
    sharedVariables: { #Default };  
    package: 'Morphic-Core'
```

and

```
BorderStyle class  
    slots: {#default};  
    package: 'Morphic-Core'
```



Implications: One for all

```
Object << #BorderStyle  
    sharedVariables: { #Default };  
    package: 'Morphic-Core'
```

There is only one instance of `BorderStyle` for all the subclasses: `SimpleBorderStyle` `BottomBorderStyle` `ComplexBorderStyle` ...



Implications: One for each

```
BorderStyle class  
slots: {#default};  
package: 'Morphic-Core'
```

There is one instance for *EACH* of all the subclasses (potentially the same depending on the creation logic)



Conclusion

- Pay attention modifying shared variables potentially impacts many objects
- Can be used to support different sharing optimization (see other Lectures)

Produced as part of the course on <http://www.fun-mooc.fr>

Advanced Object-Oriented Design and Development with Pharo

A course by
S.Ducasse, L. Fabresse, G. Polito, and P. Tesone



Except where otherwise noted, this work is licensed under CC BY-NC-ND 3.0 France
<https://creativecommons.org/licenses/by-nc-nd/3.0/fr/>